

Cylindrical Lithium Battery Cell



■ Main application scene



Power Tools



Smart Appliances



IoT



AGV



E-Motorcycle



E-Bike



Electrical forklift



Key Benefits

- High energy density
- High rate continuous discharge
- Supports fast charging
- Excellent high and low temperature cycling
- Long service life and long cycle life
- Meet safety certification, reliable security

Specifications

Models	Nominal Voltage (V)	Nominal Capacity (mAh)	Charging cutoff voltage (V)	Discharging cutoff voltage (V)	Max. charging current (A)	Max. discharging current (A)	Size (mm)		Weight (g)
							Diameter	Heigh	
18650P-2000mAh	3.7	2000	4.2	2.75	4	30	18.4±0.2	65.0±0.2	43.0
18650H-2000mAh	3.6	2000	4.2	2.75	6	30	18.4±0.2	65.0±0.2	43.5
18650P-2200mAh	3.7	2200	4.2	2.75	4	22	18.4±0.2	65.0±0.2	45.0
18650P-2500mAh	3.7	2500	4.2	2.75	4	30	18.4±0.2	65.0±0.2	45.0
18650P-2600mAh	3.7	2600	4.2	2.75	2.6	13	18.4±0.2	65.0±0.2	45.0
18650H-3000mAh	3.6	3000	4.2	2.5	4	25	18.4±0.2	65.0±0.2	46.0
21700P-4000mAh	3.6	4000	4.2	2.5	4	20	21.2±0.2	70.5±0.2	65.0
21700H-4000mAh	3.6	4000	4.2	2.5	6	40	21.2±0.2	70.5±0.2	65.0
21700E-5000mAh	3.6	5000	4.2	2.5	5	15	21.2±0.2	70.5±0.2	70.5

Products specifications described herein are subject to change without prior notification.

Shandong Sacred Sun Power Sources Co., Ltd.

No.1 Shengyang Road, Qufu 273100, Shandong Province, China
sales@sacredsuns.cn

Shandong Sacred Sun Lico Tech EnergyCo.,Ltd

No. 1999,Yitianmen Street,Taian High tech Zone, Shandong Province, China
sales@sacredsuns.cn