

# HRL Series

## HRL12-700W 12V195Ah

Sacred Sun HRL batteries adopt new appearance and constructure design, automatic welding+through the partition welding+heat sealing technology, full automatic production process with good consistency. It has excellent high power discharge, long floating backup time and fast charging performance. It can be widely used in data center, UPS, IDC room.

### Benefits

- Very long life according to EUROBAT Classification
- High power density, 30% higher than ordinary batteries
- Special lead paste formula and additives improve the battery service life
- Maximum charge efficiency
- Low self-discharge rate
- Wide range of power, easy sizing of batteries
- Easy installation and handling


### Applications

- Data center
- UPS
- IDC room
- Emergency power
- HVDC system

### Standards

- IEC 60896-21/22
- JIS C8704-1/2
- EUROBAT guide

### Drawing



### Specifications


|                                      |                                                          |               |                       |                    |
|--------------------------------------|----------------------------------------------------------|---------------|-----------------------|--------------------|
| Battery Model                        | HRL12-700W                                               |               |                       |                    |
| Design Life (years, 25°C)            | 15                                                       |               |                       |                    |
| Capacity (Ah, 25°C)                  | 10min (1.60V)                                            | 15min (1.67V) | 1HR (120A, 1.70V)     | 10HR(19.5A, 1.80V) |
|                                      | 860W/cell                                                | 700W/cell     | 120                   | 195                |
| Dimensions (mm)                      | Length                                                   | Width         | Height                | Total Height       |
|                                      | 530                                                      | 232           | 233                   | 240                |
| Approx. Weight (kg)                  | 64.8                                                     |               |                       |                    |
| Reference Internal Resistance (mΩ)   | 2.0±15%( full charged @ 25°C,testing device:HIOKIBT3562) |               |                       |                    |
| Maximum Discharge Current (A/3 Sec.) | 2100                                                     |               |                       |                    |
| Self-Discharge (25°C)                | ≤ 2% per month                                           |               |                       |                    |
| Charge Voltage (V/cell, 25°C)        | Cycle use                                                |               | Float use             |                    |
|                                      | 2.35 (-3.5mV/°C/cell), max charge current:48.75A         |               | 2.25 (-3.5mV/°C/cell) |                    |
| Short Circuit Current (A)            | 5400                                                     |               |                       |                    |

## Discharge Data


| Constant Power Discharge Data (25°C, W/cell) |      |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |
|----------------------------------------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|
| End Voltage (V/cell)                         | min  |     |     |     |     |     |     | h   |     |     |     |      |      |      |      |      |
|                                              | 5    | 10  | 15  | 20  | 25  | 30  | 45  | 1   | 1.5 | 2   | 3   | 4    | 5    | 6    | 8    | 10   |
| 1.60                                         | 1100 | 860 | 727 | 597 | 510 | 422 | 318 | 230 | 192 | 160 | 117 | 89.4 | 72.0 | 62.2 | 48.8 | 40.4 |
| 1.65                                         | 1000 | 847 | 712 | 587 | 503 | 417 | 317 | 238 | 191 | 159 | 116 | 88.8 | 71.8 | 62.0 | 48.6 | 40.3 |
| 1.67                                         | 980  | 820 | 700 | 578 | 498 | 413 | 315 | 236 | 189 | 158 | 115 | 88.5 | 71.6 | 61.8 | 48.5 | 40.2 |
| 1.70                                         | 950  | 797 | 680 | 566 | 490 | 408 | 312 | 234 | 188 | 157 | 114 | 87.8 | 71.4 | 61.6 | 48.3 | 40.0 |
| 1.75                                         | 920  | 742 | 640 | 540 | 474 | 396 | 306 | 226 | 183 | 154 | 112 | 86.6 | 70.8 | 61.2 | 48.0 | 39.7 |
| 1.80                                         | 870  | 675 | 600 | 508 | 453 | 362 | 290 | 204 | 168 | 140 | 106 | 85.0 | 70.3 | 60.6 | 46.5 | 38.4 |

| Constant Current Discharge Data (25°C, A) |     |     |     |     |     |     |     |     |      |      |      |      |      |      |      |      |
|-------------------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|
| End Voltage (V/cell)                      | min |     |     |     |     |     |     | h   |      |      |      |      |      |      |      |      |
|                                           | 5   | 10  | 15  | 20  | 25  | 30  | 45  | 1   | 1.5  | 2    | 3    | 4    | 5    | 6    | 8    | 10   |
| 1.60                                      | 620 | 524 | 395 | 322 | 274 | 225 | 168 | 125 | 100  | 83.0 | 60.5 | 46.0 | 36.8 | 31.8 | 24.8 | 20.5 |
| 1.65                                      | 580 | 508 | 386 | 316 | 268 | 220 | 166 | 123 | 98.5 | 82.0 | 59.8 | 45.6 | 36.7 | 31.6 | 24.7 | 20.4 |
| 1.67                                      | 560 | 495 | 378 | 310 | 266 | 218 | 165 | 122 | 97.5 | 81.3 | 59.2 | 45.2 | 36.5 | 31.4 | 24.5 | 20.3 |
| 1.70                                      | 550 | 478 | 368 | 303 | 260 | 215 | 163 | 120 | 96.2 | 80.3 | 58.4 | 44.8 | 36.3 | 31.2 | 24.4 | 20.2 |
| 1.75                                      | 510 | 438 | 346 | 286 | 248 | 206 | 158 | 117 | 93.2 | 77.8 | 56.6 | 43.7 | 35.7 | 30.8 | 24.0 | 19.8 |
| 1.80                                      | 470 | 394 | 320 | 267 | 236 | 197 | 152 | 113 | 89.7 | 75.0 | 54.5 | 42.5 | 35.0 | 30.2 | 23.6 | 19.5 |


## Performance Curve




Charge performance



Discharge voltage vs. discharge time



Temperature vs. charge voltage



Design life vs. temperature

### Sacred Sun Power Sources Co., Ltd.

Add: No.1 Shengyang Road, Qufu 273100 PRC  
 Tel: +86-537-4422313 Fax: +86-537-4411980  
 Email: sales@sacredsunsun.cn

### Sacred Sun Hong Kong Co., Limited

Add: RM 19C Lockhart CTR 301-307 Lockhart RD Wan Chai, Hong Kong  
 Email: admin.hk@sacredsunsun.hk

### Sacred Sun Asia Pacific Pte Ltd.

Add: 1 Ubi View, #04-12, Focus One, Singapore 408555  
 Email: admin.sg@sacredsunsun.sg

### Sacred Sun Europe SARL

Add: ZAE Fontaine, 33210 Fargues, France  
 Email: admin.eu@sacredsunsun.eu

### Sacred Sun MEA FZE

Add: No. 311 office, Building LOB 14, JAFZA, Dubai, UAE  
 Email: admin.ae@sacredsunsun.ae

