

HRL Series

HRL12-550W 12V140Ah

Sacred Sun HRL batteries adopt new appearance and constructure design, automatically welding+through the partition welding+heat sealing technology, full automatic production process with good consistency. It has excellent high power discharge, long floating backup time and fast charging performance. It can be widely used in data center, UPS, IDC room.

Benefits

- Very long life according to EUROBAT Classification
- High power density, 30% higher than ordinary batteries
- Special lead paste formual and additives improve the battery service life
- Maximum charge efficiency
- Low self-discharge rate
- Wide range of power, easy sizing of batteries
- Easy installation and handling


Applications

- Data center
- UPS
- IDC room
- Emergency power
- HVDC system

Standards

- IEC 60896-21/22
- JIS C8704-1/2
- EUROBAT guide

Drawing



Specifications


Battery Model	HRL12-550W			
Design Life (years, 25°C)	15			
Capacity (Ah, 25°C)	10min (1.60V)	15min (1.67V)	1HR (87A, 1.70V)	10HR(14.0A, 1.80V)
	635W/cell	550W/cell	87	140
Dimensions (mm)	Length	Width	Height	Total Height
	483	174	219	227
Approx. Weight (kg)	46.5			
Reference Internal Resistance (mΩ)	2.2±15%(full charged @ 25°C,testing device:HIOKIBT3562)			
Self-Discharge (25°C)	≤ 2% per month			
Charge Voltage (V/cell, 25°C)	Cycle use		Float use	
	2.35 (-3.5mV/°C/cell), max charge current:35A		2.25 (-3.5mV/°C/cell)	
Short Circuit Current (A)	4300(For reference only)			

Discharge Data


Constant Power Discharge Data (25°C, W/cell)																	
End Voltage (V/cell)	min							h									
	5	10	15	20	25	30	45	1	1.5	2	3	4	5	6	8	10	
1.60	780	635	560	444	374	312	243	174	140	116	82.4	63.8	52.7	45.4	35.4	29.6	
1.65	770	630	555	438	370	308	240	173	139	115	82.0	63.5	52.4	45.2	35.2	29.4	
1.67	760	620	550	435	366	306	238	171	138	114	81.6	63.2	52.2	45.0	35.0	29.3	
1.70	750	610	530	426	360	302	235	170	137	113	81.2	62.8	51.8	44.7	34.8	29.0	
1.75	720	590	500	416	350	294	228	165	134	110	80.0	62.0	51.3	44.2	34.4	28.7	
1.80	660	550	460	400	336	283	220	160	131	108	78.8	61.0	50.5	43.5	33.8	28.3	

Constant Current Discharge Data (25°C, A)																	
End Voltage (V/cell)	min							h									
	5	10	15	20	25	30	45	1	1.5	2	3	4	5	6	8	10	
1.60	440	364	300	245	203	166	128	91.0	72.6	59.6	42.5	32.8	27.0	23.2	18.0	15.0	
1.65	420	356	295	240	200	164	126	89.0	71.8	59.0	42.0	32.5	26.8	23.0	17.8	14.9	
1.67	410	348	290	237	197	162	124	88.0	71.0	58.5	41.8	32.3	26.6	22.8	17.7	14.8	
1.70	400	340	283	233	193	158	122	87.0	70.2	57.8	41.4	32.0	26.4	22.7	17.6	14.7	
1.75	365	318	270	222	185	153	118	84.0	68.2	56.4	40.5	31.3	25.8	22.2	17.2	14.4	
1.80	340	294	255	210	175	145	112	80.5	65.8	54.6	39.5	30.5	25.2	21.7	16.8	14.0	


Performance Curve




Charge performance



Discharge voltage vs. discharge time



Temperature vs. charge voltage



Design life vs. temperature

Sacred Sun Power Sources Co., Ltd.

Add: No.1 Shengyang Road, Qufu 273100 PRC
Tel: +86-537-4422313 Fax: +86-537-4411980
Email: sales@sacredsun.cn

Sacred Sun Hong Kong Co., Limited

Add: RM 19C Lockhart CTR 301-307 Lockhart RD Wan Chai, Hong Kong
Email: admin.hk@sacredsun.hk

Sacred Sun Asia Pacific Pte Ltd.

Add: 1 Ubi View, #04-12, Focus One, Singapore 408555
Email: admin.sg@sacredsun.sg

Sacred Sun Europe SARL

Add: ZAE Fontaine, 33210 Fargues, France
Email: admin.eu@sacredsun.eu

Sacred Sun MEA FZE

Add: No. 311 office, Building LOB 14, JAFZA, Dubai, UAE
Email: admin.ae@sacredsun.ae

